

PDG-DXL100



Projektor s ultrakrátkou projekční vzdáleností

5-ti segmentový barevný kotouček

České menu

HDMI vstup

Životnost lampy až 4000 hodin (v Eco modu)

Rozlišení XGA 1024 x 768 bodů

Připojení RJ45 pro začlenění do strukturovaných sítí

Světelný výkon 2700 ANSI Lm, kontrastní poměr 750:1

Automatické nastavení zajišťující provoz během několika vteřin



Think GAIA
 For Life and the Earth

TECHNICAL DATA	PDG-DXL100
EAN Code	4994334270177
Category	Business & Education
Panel	1 x 0.55" DMD Chip (4:3)
Lamp	225 W UHP (LMP-139)
Brightness	2700 ANSI lumens
Brightness (eco mode)	1917 ANSI lumens
Lamp life	4000 h (eco mode) / 3000 h (normal mode)
Fan noise	29 dB (eco mode) / 34 dB (normal mode)
Standard lens	F = 2.6 / f = 6.97 mm *
Throw distance ratio	0.6 : 1
Throw distance	0.5 - 3.72 m
Contrast ratio	750 : 1
Resolution in pixels	1,024 x 768 (XGA)
Image size min. - max. (diagonal):	40 - 300 inch
Uniformity	80 %
Bandwidth/Frequency	170 MHz, Horizontal frequency: 31 - 80 kHz, Vertical frequency: 50 - 75 Hz
Color systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: HDMI (HDCP) Input 2: D-Sub15 (RGB) Input 3: D-Sub15 (RGB) Input 4: RCA (composite) Input 5: Mini DIN 4 (S-Video) Audio: 3.5 mm stereo jack Audio output: 3.5 mm stereo jack Monitor output: D-Sub15 Control input jack 1: RJ45 (LAN) Control input jack 2: Mini DIN 8 (RS232)
Audio function	8 W mono
Keystone correction	vertical +/- 15°
Up/Down ratio	20 : -3 (fixed U/D ratio)
HDTV compatibility	480i, 480p, 575i, 575p, 720p, 1,080i, 1,080p
Computer compatibility	UXGA, SXGA, WXGA, XGA, SVGA, VGA
Zoom/Focus	1.0 x/manual
Power consumption	240 W (eco mode) / 320 W (normal mode), 0.9 W (stand-by mode)
Voltage	100 - 240 V
Dimensions (W x H x D)	306.5 x 105.0 x 292.3 mm
Weight (net)	3.7 kg
Standard accessories	IR remote control, Batteries, User manual, Power cable, D-Sub15 cable, Lens cover with cord
Optional accessories	SCART/D-Sub15 cable (POA-CA-SCART), Components/D-Sub15 cable (POA-CA-COMPVGA), Ceiling mount 15 cm (POA-CM01), Ceiling mount 40-70 cm (POA-CM02), Ceiling mount 70-110 cm (POA-CM03)
Lenses	Standard lens

