

PLC-WXU10



Formát obrazu 16 : 10 - vhodný pro stále častěji používané širokoúhlé monitory notebooků i velkoplošnou projekci domácího kina

Rozlišení 1280 x 800 bodů (WXGA)

Světelný výkon 2000 ANSI Lm, kontrastní poměr 400:1

Široké možnosti připojení, včetně DVI-D s HDCP

Plynule nastavitelná velikost obrazu až 7,62 m (úhlopříčka)



Think GAIA
For Life and the Earth

TECHNICAL DATA	PLC-WXU10
Category	Business & Education
Panel	0.56" TFT p-Si (16 : 10), micro lens
Projection Lamp	210 W NSH (LMP-113)
Brightness in ANSI lumens	2,000
Lamp Life	3,000 h (eco mode)/2,000 h (normal mode)
Fan noise	32 dB (eco mode)/35 dB (normal mode)
Standard Lens	F = 1.75–1.9/f = 18.85–22.23 mm*
Throw Distance Ratio	1.5–1.8 : 1*
Throw Distance	1.32–11.6 m*
Image size min–max (diagonal)	40"–300"
Contrast Ratio	400 : 1
Resolution in pixels	1,280 x 800 (WXGA)
Uniformity	80 %
Bandwidth/Frequency	110 MHz, horizontal 15–80 kHz, vertical 50–85 Hz
Colour Systems	PAL/SECAM/NTSC/NTSC4.43/PAL-M/N
Connections	Input 1: D-Sub15 Input 2: DVI-D (digital/HDCP) Input 3: RCA (Composite) Input 4: Mini DIN 4-pin (S-Video) Input 5: 3 x Cinch (Y-Pb/Cb-Pr/Cr) Audio: 2 x RCA (R/L mono) Monitor Output: D-Sub15 Control Input Jack: Mini DIN 8-pin (RS232 compatible)
Audio Function	2 W Mono
Keystone Correction	vertical +/-16°
Up/Down-Ratio	100 : -1 (Fixed U/D Ratio)
HDTV Compatibility	480i/480p/576i/576p/720p/1,080i
Computer Compatibility	SXGA/WXGA/XGA/SVGA/VGA
Zoom/Focus	1.2 x/manual focussing
Power Consumption/Voltage	240 W (eco mode)/280 W (normal mode)/5 W (stand-by mode)
Dimensions (W x H x D)	298 x 98 x 237 mm
Weight	3.3kg
Standard Accessories	IR remote control, batteries, user manual (CD-ROM), D-Sub15 cable, power cable, lens cap, carrier bag
Optional Accessories	Components/D-Sub15 cable (POA-CA-COMPVGA), ceiling mounts: 15 cm (POA-CM01), 40–70 cm (POA-CM02), 70–110 cm (POA-CM03)
Lenses	Standard lens

