

## PLC-XU355



**Bezdrátové připojení k síti Wi-Fi a LAN připojení (RJ45)**

**Snadné nastavení sítě pro rychlé a jednoduché připojení do sítě LAN nebo bezdrátových sítí (bezinstalační proces)**

**Vestavěný reproduktor s výkonem 7 W**

**Vstup DVI-I včetně HDCP protokolu**

**USB připojení pro prezentace bez PC**

**Světelný výkon 3500 ANSI lm, kontrastní poměr 500 : 1**

**1,6 x optický zoom**

**Rozlišení XGA (1024 x 768 bodů) ve formátu 4 : 3**

**Nízká hluchnost: 29db (eco mod)**

## PLC-XU355

TECHNICAL DATA	PLC-XU355
EAN Code	4994334266187
Category	Business & Education
Panel	3 x 0.63" TFT p-Si (4:3), micro lens
Panel type	Organic LCD panel
Lamp	225 W UHP (LMP-131)
Brightness	3500 ANSI lumens
Brightness (eco mode)	2450 ANSI lumens
Lamp life	2500 h (eco mode) / 2000 h (normal mode)
Fan noise	29 dB (eco mode) / 34 dB (normal mode)
Standard lens	F = 1.65 - 2.33 / f = 15.47 - 24.53 mm *
Throw Distance Ratio	1.18 - 1.91 : 1
Throw Distance	0.69 - 7.23 m
Contrast ratio	500 : 1
Resolution in pixels	1,024 x 768 (XGA)
Image size min. - max. (diagonal):	30 - 300 inch
Uniformity	85 %
Bandwidth/Frequency	140 MHz, Horizontal : 15 - 100 kHz, Vertical : 50 - 100 Hz
Colour systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: DVI-I (digital/HDCP/analogue) Input 2: D-Sub15 (RGB/Component/SCART-RGB) Input 3: RCA (Video) Input 4: Mini DIN 4 (S-Video) Input 5: RJ45 (LAN) Audio: 3.5 mm Stereo Jack Audio: 2 x RCA (R/L mono) Audio output : 3.5 mm Stereo Jack Monitor output: D-Sub15 Control Input Jack 1: D-Sub9 (RS232) Control Input Jack 2: USB type B (Mouse Control) Others: USB type A (USB-Key)
Audio function	7 W mono
Keystone correction	vertical +/- 30°
Up/Down Ratio	9:1 (Fixed U/D Ratio)
HDTV compatibility	480i, 480p, 575i, 575p, 720p, 1,080i
Computer compatibility	U-XGA, S-XGA, S-XGA+, W-XGA, XGA, S-VGA, VGA, Mac
Zoom/Focus	1.6 x/manual
Power consumption	240 W (eco mode) / 310 W (normal mode), 4.4 W (stand-by mode)
Voltage	100 - 240 V
Dimensions (W x H x D)	326.0 x 92.6 x 266.8 mm
Weight (Net)	2.9 kg
Standard accessories	IR remote control, Batteries, User manual, Power cable, D-Sub15 cable, PIN code label, Carrier bag, Lens cover with cord, CD-ROM for network module, USB stick with software for Easy Network Set-Up
Optional accessories	SCART/D-Sub15 cable (POA-CA-SCART), Components/D-Sub15 cable (POA-CA-COMPVGA), Ceiling mount 15 cm (POA-CM01), Ceiling mount 40-70 cm (POA-CM02), Ceiling mount 70-110 cm (POA-CM03)
Lenses	Standard lens

